



FORM PTO-1300 (REV 10-96)		U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE		ATTORNEY'S DOCKET NUMBER  32107	
<b>TRANSMITTAL LETTER TO THE UNITED STATES DESIGNATED/ELECTED OFFICE (DO/EO/US) CONCERNING A FILING UNDER 35 U.S.C. 371</b>				U.S. APPLICATION NO. (if known, see 37 CFR 1.5) <b>09/445710</b>	
INTERNATIONAL APPLICATION NO. PCT/FI98/00509		INTERNATIONAL FILING DATE 12 June 1998 (12.06.98)		PRIORITY DATE CLAIMED 13 June 1997 (13.06.97)	
TITLE OF INVENTION <b>A PROCESS FOR STABILIZING THE pH OF A PULP SUSPENSION AND FOR PRODUCING PAPER FROM</b>					
APPLICANT(S) FOR DO/EO/US <span style="float: right;">THE STABILIZED PULP</span> <b>LEINO, Hannu, Juhani; HOLMBERG, Anna, Linnea</b>					
Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:					
1. <input checked="" type="checkbox"/> This is a <b>FIRST</b> submission of items concerning a filing under 35 U.S.C. 371. 2. <input type="checkbox"/> This is a <b>SECOND</b> or <b>SUBSEQUENT</b> submission of items concerning a filing under 35 U.S.C. 371. 3. <input type="checkbox"/> This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1). 4. <input checked="" type="checkbox"/> A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date. 5. <input checked="" type="checkbox"/> A copy of the International Application as filed (35 U.S.C. 371(c)(2)) a. <input type="checkbox"/> is transmitted herewith (required only if not transmitted by the International Bureau). b. <input checked="" type="checkbox"/> has been transmitted by the International Bureau. c. <input type="checkbox"/> is not required, as the application was filed in the United States Receiving Office (RO/US). 6. <input checked="" type="checkbox"/> A translation of the International Application into English (35 U.S.C. 371(c)(2)). 7. <input checked="" type="checkbox"/> Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3)) a. <input type="checkbox"/> are transmitted herewith (required only if not transmitted by the International Bureau). b. <input type="checkbox"/> have been transmitted by the International Bureau. c. <input type="checkbox"/> have not been made; however, the time limit for making such amendments has NOT expired. d. <input checked="" type="checkbox"/> have not been made and will not be made. 8. <input type="checkbox"/> A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)). 9. <input type="checkbox"/> An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)). 10. <input checked="" type="checkbox"/> A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).					
Items 11. to 16. below concern document(s) or information included:					
11. <input type="checkbox"/> An Information Disclosure Statement under 37 CFR 1.97 and 1.98. 12. <input type="checkbox"/> An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included. 13. <input type="checkbox"/> A FIRST preliminary amendment. <input type="checkbox"/> A SECOND or SUBSEQUENT preliminary amendment. 14. <input type="checkbox"/> A substitute specification. 15. <input type="checkbox"/> A change of power of attorney and/or address letter. 16. <input checked="" type="checkbox"/> Other items or information: Copy of the International Preliminary Examination Report.					
				"Express Mail" mailing label number <u>EL384023275US</u> Date of Deposit <u>12/9/99</u> I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 C.F.R. § 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.	
				Paula Almasy Printed Name of Person Mailing Paper or Fee  Signature of Person Mailing Paper or Fee	

U.S. APPLICATION NO. (if known) <b>09/445710</b>		INTERNATIONAL APPLICATION NO. <b>PCT/FI98/00509</b>		ATTORNEY'S DOCKET NUMBER <b>32107</b>	
17. <input checked="" type="checkbox"/> The following fees are submitted: <b>BASIC NATIONAL FEE ( 37 CFR 1.492 (a) (1) - (5) ) :</b> Search Report has been prepared by the EPO or JPO ..... <b>\$910.00</b>  International preliminary examination fee paid to USPTO (37 CFR 1.482) ..... <b>\$700.00</b>  No international preliminary examination fee paid to USPTO (37 CFR 1.482) but international search fee paid to USPTO (37 CFR 1.445(a)(2)) ..... <b>\$770.00</b>  Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO ..... <b>\$1040.00</b>  International preliminary examination fee paid to USPTO (37 CFR 1.482) and all claims satisfied provisions of PCT Article 33(2)-(4) ..... <b>\$96.00</b>				<b>CALCULATIONS PTO USE ONLY</b>	
<b>ENTER APPROPRIATE BASIC FEE AMOUNT =</b>				<b>\$ 840.00</b>	
Surcharge of <b>\$130.00</b> for furnishing the oath or declaration later than <input type="checkbox"/> 20 <input checked="" type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(e)).				<b>\$ 130.00</b>	
CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE		
Total claims	12 - 20 =	0	X \$22.00	\$ -0-	
Independent claims	2 - 3 =	0	X \$80.00	\$ -0-	
MULTIPLE DEPENDENT CLAIM(S) (if applicable)			+ \$260.00	\$ -0-	
<b>TOTAL OF ABOVE CALCULATIONS =</b>				<b>\$ 970.00</b>	
Reduction of 1/2 for filing by small entity, if applicable. Verified Small Entity Statement must also be filed (Note 37 CFR 1.9, 1.27, 1.28).				\$ -0-	
<b>SUBTOTAL =</b>				<b>\$ 970.00</b>	
Processing fee of <b>\$130.00</b> for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(f)).				\$ -0-	
<b>TOTAL NATIONAL FEE =</b>				<b>\$ 970.00</b>	
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). <b>\$40.00</b> per property				\$ -0-	
<b>TOTAL FEES ENCLOSED =</b>				<b>\$ 970.00</b>	
				Amount to be: refunded	\$
				charged	\$
a. <input checked="" type="checkbox"/> A check in the amount of \$ <u>970.00</u> to cover the above fees is enclosed.  b. <input type="checkbox"/> Please charge my Deposit Account No. _____ in the amount of \$ _____ to cover the above fees. A duplicate copy of this sheet is enclosed.  c. <input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. <u>16-0820</u> . A duplicate copy of this sheet is enclosed. <div style="text-align: center;">Our Order No. 32107</div>					
<b>NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.</b>					
SEND ALL CORRESPONDENCE TO <b>Jeffrey J. Sopko</b> <b>Pearne, Gordon, McCoy &amp; Granger LLP</b> <b>526 Superior Avenue, East</b> <b>Suite 1200</b> <b>Cleveland, Ohio 44114-1484</b>					
				SIGNATURE	NAME
					<b>Jeffrey J. Sopko</b>
				<b>27676</b>	REGISTRATION NUMBER

A process for stabilizing the pH of a pulp suspension and for producing paper from the stabilized pulp

The invention relates to a process for stabilizing the pH of a paper making pulp suspension with buffering agents and to a process for producing paper from such a stabilized pulp suspension.

During the last ten to fifteen years many paper makers have converted their processes from acidic to neutral pH for a number of reasons, e.g. to gain increased strength and to be able to use calcium carbonate,  $\text{CaCO}_3$ , as a filler. The expression "neutral pH" corresponds in these processes to a pH in the short circulation of approximately 7-8.5, most preferably 7-8. This applies to paper produced from chemical, mechanical and recycled pulp, bleached or unbleached.

If the paper making pulp is acidic when entering the stock preparation and the short circulation is run at a neutral or alkaline pH, the traditional way of raising and controlling the pH is to add sodium hydroxide, NaOH. NaOH is, however, a very strong base, which means that only small amounts are needed for pH adjustments. Any over-dosage will cause a too big pH increase, which means that it is difficult to perform the pH adjustment in a controlled way. This is due to the low inherent buffering ability of a pulp suspension. The paper maker could end up in a situation with varying pH of the entering pulp, which has a negative impact on paper quality and paper machine runnability.

Through the stock preparation and the short circulation a number of paper chemicals and dilution waters are added, some of which are acidic and therefore decrease the pH of the pulp. The paper maker could therefore end up with a too low pH in the short circulation and would be once again forced to pH adjust using NaOH. The pH may also change at refining or in storage towers.

If the paper making pulp is alkaline instead when entering the stock preparation and if the short circulation is run at a neutral or alkaline pH, there is naturally no need to use any NaOH for pH control. The paper maker must however make sure that the pH is high enough to avoid ending up with too low a pH after addition of acidic paper chemicals.

In the prior art one way of avoiding ending up with too low pH values has been to add dissolved sodium bicarbonate,  $\text{NaHCO}_3$ , to the pulp. The  $\text{NaHCO}_3$  dissociates in the pulp

09/445710-034300


suspension forming bicarbonate ions,  $\text{HCO}_3^-$ , which have a buffering effect and therefore counteract any pH decrease.  $\text{NaHCO}_3$  is a solid powder, which is generally supplied in so called big-bags, and the paper mill needs space for handling, equipment for dissolving and tanks for storage. The  $\text{NaHCO}_3$  is messy to work with, when in contact with moisture or water.

In the non-acidic sizing of paper with alkylketene dimers bicarbonate ions have been used to catalyze the reaction between the alkylketene dimers and the cellulose. According to US Patent 5,378,322 the bicarbonate ions may be generated by dissociation of carbon dioxide  $\text{CO}_2$  in the aqueous pulp.

Carbon dioxide is a gas, which easily dissolves under alkaline conditions, e.g. in water or a pulp suspension forming carbonic acid and/or bicarbonate ions according to the reaction:



At a high pH, especially greater than 10, the predominant reaction is



In the recycling of gypsum-containing waste or broke paper the accumulation of calcium sulfate poses a problem since the solubilized calcium sulfate may precipitate and disturb the paper making process. According to US Patent 5,262,006 this problem may be overcome by adding carbonate ions and/or bicarbonate ions to the aqueous pulp suspension and by adjusting the pH to an alkaline value to precipitate the calcium as calcium carbonate. The bicarbonate ions may be created *in situ* for example by first adding a suitable soluble metal hydroxide and then adding carbon dioxide. According to the Patent, the calcium carbonate generation from calcium sulfate with carbon dioxide requires a close control of the pH since carbon dioxide has the effect of lowering the pH so that there is a risk of the pH becoming too low for the carbonation process.

Carbon dioxide has also been used for the pH control of pulp suspensions, for instance, in a process described in EP Patent 0 281 273, wherein gaseous carbon dioxide is introduced to adjust and maintain the pH at a value which is preferably between 7.0 and 5.5.

Thus, in the prior art carbon dioxide has been used to create bicarbonate ions for its catalyzing, carbonating or pH lowering effect. However, a paper maker also has the need

to obtain a stable pH so that chemical additions and various processing steps do not cause an unwanted fluctuation of the pH.

An object of the present invention is thus to provide a pH stabilization of aqueous pulp suspensions.

Another object of the invention is to provide a paper making pulp suspension having an increased alkalinity, i.e. a resistance to pH change.

A further object of the invention is to provide a technically advantageous process for buffering a pulp suspension.

An object is also to provide a pulp suspension having a controlled pH which is maintained at a desired level.

An object of the invention is also to provide a process for producing paper from a pulp suspension having a stabilized pH.

The invention according to the present application is defined in the appended claims, the contents of which are included herein by reference.

Consequently, the present invention relates to a process for stabilizing the pH of a pulp suspension, wherein the alkalinity of a paper making pulp suspension is increased by adding thereto a combination of an alkali metal hydroxide feed and a carbon dioxide feed which feeds substantially counter each other's pH changing effect, said feeds being provided in an amount sufficient to achieve a significant buffering effect of said pulp suspension for paper making.

The feeding of a hydroxide and carbon dioxide in substantially countering amounts increases the level of alkalinity forming ions in the suspension without actually affecting its pH. Increasing the alkalinity stabilizes the suspension against pH fluctuations caused by subsequent additions of acidic or basic fluids and provides a stable pH throughout the succeeding steps.

Alkalinity is a measurement of "acid resistance", i.e. the content of buffering ions in a liquid or pulp suspension, which counteracts pH decrease at addition of hydrogen ions,  $H^+$ . One way of expressing alkalinity is the amount of  $HCO_3^-$  and  $CO_3^{2-}$  ions in grams

09445710 "034300"

per liter. When a combination of hydroxide and carbon dioxide is used according to the present invention, the alkalinity of the pulp suspension is raised, thus creating larger "acid resistance".

The hydroxide used according to the invention should preferably be added prior to the addition of the carbon dioxide to ensure that the carbon dioxide is added under alkaline conditions.

The "amount sufficient to achieve a significant buffering effect" should be taken as meaning an amount providing a substantial and recognizable buffering effect in the pulp suspension. The amount normally varies depending on the characteristics of the pulp and on the conditions of treatment. A person skilled in the art will be able to calculate the required amount based on his general knowledge or by simple tests made on the actual pulp suspension, as indicated, for example in Example 9 of this specification.

Typically the amount of NaOH in the buffering combination will be between about 0.5 and 5 kg NaOH/ton dry cellulose and the amount of carbon dioxide in said combination will be between about 0.5 and 5 kg CO<sub>2</sub>/ton dry cellulose. A typical buffering combination would include about 2 to 3 kg of NaOH and CO<sub>2</sub> per ton of dry cellulose. It is within the scope of the present invention to use more or less than the above mentioned amounts of both components, but in general it will be uneconomical to use more than what is required for a desired buffering action.

It is clear that the excess of either NaOH or CO<sub>2</sub> which is additionally used for pH adjusting purposes may significantly exceed the above amounts which provide the buffering effect.

The buffering effect obtained by the addition of NaOH and CO<sub>2</sub> in this way corresponds to the one obtainable by an addition of dissolved NaHCO<sub>3</sub> but it has the advantage that the space consuming and messy handling of solid NaHCO<sub>3</sub> is avoided. Sodium hydroxide, on the other hand, is a chemical which is abundantly available in the paper mill since it is used for many other purposes. Carbon dioxide gas may be generated on site or may be bought as desired. Feeding of carbon dioxide into the suspension is technically clean and easy.

A further advantage resides in that the hydroxide and carbon dioxide used according to the present invention may serve the dual purpose of increasing the alkalinity and of adjusting

the pH. Thus, according to a preferred embodiment of the invention, the pH of said pulp suspension is increased by adding an excess of alkali metal hydroxide such as aqueous sodium hydroxide or decreased by adding an excess of carbon dioxide.

The carbon dioxide is preferably in gaseous form, although it may be added as an aqueous liquid by dissolving gaseous or solid carbon dioxide in water. The hydroxide and carbon dioxide may be combined prior to feeding to the pulp suspension although it is preferred to feed them directly into the pulp circulation system such as to a pipe leading to a stock preparation tank.

The pulp suspension is preferably buffered by said combination to a pH between about 7 and 9.

According to the preferred embodiment of the invention the alkalinity of the pulp suspension is increased by providing a substantially equal molar amount of alkali metal hydroxide and dissolved carbon dioxide, said amount being sufficient to provide a significant buffering effect at about pH 8.

The pulp suspension may be bleached or unbleached chemical or mechanical pulp although the preferred pulp is bleached chemical pulp.

Calcium carbonate may advantageously be used as a filler for the pulp, since the stabilized pH will ascertain that the filler remains in solid form in the suspension. A fluctuation of the pH down to 6 or 5.5, for instance due to an inflow of circulating white water at such a pH, might dissolve the carbonate filler. Such an undesirable effect will be effectively prevented by the buffering action of the present invention.

The present invention also relates to a process for producing paper, said process comprising the steps of

- providing a paper making pulp suspension;
- increasing the alkalinity of said pulp suspension by adding thereto a combination of an alkali metal hydroxide feed and a carbon dioxide feed which feeds substantially counter each others pH changing effect, said feeds being provided in an amount sufficient to achieve a substantial buffering effect of said pulp suspension for paper making;
- optionally adjusting the pH of said pulp suspension to a desired value between 7 and 9 by adding an alkaline agent such as NaOH or an acidic agent such as CO<sub>2</sub>;
- forming said pulp suspension into a web; and

09445710-034300

- drying said web to form paper.

The production of paper according to the present invention is performed in a conventional way in all other respects except for the increase of the alkalinity of the pulp prior to the short circulation. Such paper making processes are well known in the art and it is not considered necessary to describe them here in any greater detail.

The invention will now be illustrated with a few examples which should not be considered as limiting the invention in any way.

### Example 1

(Reference example)

In a partly integrated paper mill bales of fully bleached kraft market pulp are introduced into a pulp slusher. The pH in the slusher is adjusted with aqueous NaOH to a pH of approximately 11.

After slushing, paper making chemicals and dilution water having an acidic effect are added to the slushed pulp suspension. As a consequence of this, the pH of the pulp suspension decreases from pH 11 to about pH 6.5-6.8. This pH is too low for the short circulation, which is run at a pH level of 7-7.5. Thus, the pH is again adjusted by an addition of aqueous NaOH.

Because of the strong basic action of NaOH it is difficult to achieve an exact pH control in this way. Over-dosing leads to a too high pH.

### Example 2

The process of Example 1 is changed in order to improve the situation, so that a combination of NaOH and CO<sub>2</sub> is added to the pulp slusher. The amount of NaOH added to the suspension is substantially increased compared to the process of Example 1. A countering amount of CO<sub>2</sub> is added to provide a pH of approximately pH 9.

After slushing, the same paper chemicals as in Example 1 are added to the slushed pulp suspension. Because of the buffering effect of the combined NaOH and CO<sub>2</sub>, the acidic additions lower the pH only to pH 7.2. This is a suitable pH for the short circulation and there is no need for any pH control using NaOH.



**Example 3**

(Reference example)

In a paper mill a kraft pulp suspension having a pH of 5.1 is fed to a storage tower. Prior to the entry into the tower, the pH of the pulp suspension is adjusted to pH 8 by an addition of aqueous NaOH into the pipe leading to the tower. The pulp suspension is fed from the storage tower to a refiner. At refining the pH decreases to about pH 6.

The low pH causes problems in the subsequent sizing of the pulp.

**Example 4**

The process of Example 3 is repeated with the exception that instead of feeding only the required amount of NaOH into the pulp suspension, an excess of NaOH is fed first into the pipe followed by feeding gaseous CO<sub>2</sub> into the pipe counteracting the excess NaOH. The resulting suspension again has a pH of 8 when entering the storage tower.

From the storage tower the pulp is fed to the refiner. At refining the pH remains at about pH 8 and there are no problems at sizing.

**Example 5**

In a laboratory trial a pulp suspension having a pH of 5.1 was used. The pH of the pulp suspension was adjusted to pH 8 by using a) only NaOH and b) by using an excess of NaOH in combination with CO<sub>2</sub>. The buffering effect of the suspension was tested with a strong acid (alum, pH 3.0).

The results are shown in Table 1 below.

Table 1

	pH <sup>1</sup>	NaOH (ml)	CO <sub>2</sub> (g)	pH <sup>2</sup>	alum (ml)	pH <sup>3</sup>
a) (NaOH)	5.1	2	-	8.0	1	6.4
b) (NaOH + CO <sub>2</sub> )	5.1	3	1	8.0	1	7.9

- 1 the pH of the initial pulp suspension
- 2 the pH after addition of NaOH / NaOH + CO<sub>2</sub>
- 3 the pH after addition of acid

In the above process 1 ml of the aqueous NaOH corresponds to about 2.5 kg/ton cellulose calculated on the dry weight basis; 1 g of CO<sub>2</sub> similarly corresponds to about 2.5 kg/ton cellulose; and 1 ml of alum corresponds to about 2.8 kg/ton cellulose.

The above results clearly show that the addition of countering amounts of NaOH and CO<sub>2</sub> stabilize the pH of the pulp suspension.

### Example 6

(Reference example)

A pulp suspension was stored in a pulp storage tank in a pulp mill at a pH of 5.5 to 6. The pulp was fed at this pH at a consistency of 3 to 4% to the paper mill via a press which increased the consistency to about 10%. The pulp was fed at this consistency to the paper mill storage tank at a pH of 5.5 to 6.

White water from the paper machine was fed to the storage tank at a pH of 7.5 to 8. The paper was produced with CaCO<sub>3</sub> as filler. Some of the filler circulated with the white water to the storage tank. When entering the storage tank the CaCO<sub>3</sub> in the white water dissolved as it met the pulp suspension at pH 5.5 to 6.

The dissolving of the CaCO<sub>3</sub> caused loss of filler and in addition thereto the calcium ions increased the hardness of the water and caused precipitations at unwanted positions.

From the storage tank the suspension was fed to a refiner. For improving the refining the pH of the pulp suspension was adjusted to 7.5 with NaOH before the refiner. Careful control of the NaOH feed was required to avoid dosing too much or too little.

In the refiner the pH decreased to 6 to 6.5 which meant increased energy consumption at refining. The pH was too low for the sizing. Thus, the pH had to be adjusted again for the sizing.

**Example 7**

(Reference example)

The process of Example 6 was repeated with the exception that aqueous  $\text{NaHCO}_3$  was fed to the paper mill storage tank to obtain the desired pH of about 7.5 to 8. The  $\text{CaCO}_3$  in the white water was not dissolved and the problem with filler loss was resolved.

The pH of the feed to the refiner was about 7.5 and no NaOH was fed to the suspension. However, in the refiner the pH decreased as before and a pH adjustment with NaOH was required for sizing.

**Example 8**

The process of Example 6 was repeated with the exception that NaOH and  $\text{CO}_2$  were fed to the pipe leading to the paper mill storage tank. The pH was adjusted to 8 and no loss of filler occurred in the storage tank.

The pH of the feed to the refiner was about 8 and no NaOH was fed to the suspension. At refining the alkalinity of the suspension counteracted the pH lowering effect in a sufficient degree to retain the pH at 7.5 to 8.

There was no need for a pH adjustment for sizing. The pulp was used for the production of paper with an excellent result.

**Example 9**

A pulp suspension having a 10% consistency and a pH of 7.4 was divided into two lots, Pulp 1 and Pulp 2, respectively, weighing 2030 g each. The pH of the pulp suspension was adjusted on one hand with sulfuric acid (a 10% by weight aqueous solution of  $\text{H}_2\text{SO}_4$ ) and on the other hand with gaseous carbon dioxide and a combination of 1 M sodium hydroxide and carbon dioxide gas.

The pH of Pulp 1 was adjusted to 6.2 with said sulfuric acid. The pH of Pulp 2 was adjusted to 6.2 by adding 15 ml sodium hydroxide and 1,02 g of carbon dioxide. The resulting pulp suspensions were titrated with 10% sulfuric acid to study their respective resistance to pH change.

The results are indicated in Table 2 below.

Table 2

Titration H <sub>2</sub> SO <sub>4</sub> (kg/t)	pH Pulp 1	pH Pulp 2
0	6.22	6.20
1.4	6.18	6.20
2.4	6.10	6.21
4.7	6.03	6.17
10.6	5.82	6.12

The sulfuric acid in Table 2 is indicated in kg of 100% H<sub>2</sub>SO<sub>4</sub> per ton of dry cellulose.

For the above adjustment of the pH and alkalinity of Pulp 2, NaOH was added in an amount of 2.9 kg/ton cellulose and CO<sub>2</sub> was used in an amount of 5.1 kg/ton cellulose. The CO<sub>2</sub> was used both for pH adjustment and to counter the addition of sodium hydroxide.

The test shows that fairly small amounts of a combination of sodium hydroxide and carbon dioxide provides an effective buffering action. The above final pH of 6.12 would render Pulp 2 fully useful for papermaking purposes, while the final pH of Pulp 1 would be too low.

It is evident that the invention may be varied in a great number of ways which are obvious to those skilled in the art without deviating from the scope of the claims.

## Claims

1. A process for stabilizing the pH of a pulp suspension in the stock preparation of a paper machine, characterized by increasing the alkalinity of said paper making pulp suspension by adding thereto a combination of an alkali metal hydroxide feed and a carbon dioxide feed which feeds substantially counter each other's pH changing effect, said feeds being provided in an amount sufficient to achieve a significant buffering effect of said pulp suspension while enabling utilization of an excess of said hydroxide or said carbon dioxide for adjusting the pH of said pulp suspension and maintaining the pH at a desired level throughout the paper making.
2. Process according to claim 1, characterized in that the pH of said pulp suspension is adjusted to a pH between about 7 and 9 by adding an excess of said alkali metal hydroxide or by adding an excess of said carbon dioxide.
3. Process according to claim 1, characterized in that said alkali metal hydroxide is aqueous sodium hydroxide and said carbon dioxide is gaseous carbon dioxide.
4. Process according to claim 1, characterized in that said alkali metal hydroxide is fed to said pulp suspension prior to the feeding of said carbon dioxide.
5. Process according to claim 1, characterized in that the alkalinity of said pulp suspension is increased by providing a substantially equal molar amount of alkali metal hydroxide and dissolved carbon dioxide, said amount being sufficient to provide a significant buffering effect at about pH 8.
6. Process according to claim 1, characterized in that said pulp suspension is chemical or mechanical pulp.
7. Process according to claim 6, characterized in that said pulp suspension is bleached chemical pulp.
8. Process according to claim 1, characterized in that said pulp suspension contains and/or is intended to contain calcium carbonate filler.

9. Process according to claim 1, characterized in that said alkali metal hydroxide and carbon dioxide feeds are added to said pulp suspension flowing in a pipe leading to a stock preparation tank.

10. Process according to claim 1, characterized in that said alkali metal hydroxide and said carbon dioxide are combined prior to feeding to the pulp suspension.

11. A process for producing paper comprising

- providing a paper making pulp suspension in the stock preparation of a paper machine;
- increasing the alkalinity of said pulp suspension by adding thereto a combination of an alkali metal hydroxide feed and a carbon dioxide feed which feeds substantially counter each others pH changing effect, said feeds being provided in an amount sufficient to achieve a substantial buffering effect of said pulp suspension while enabling utilization of an excess of said hydroxide or said carbon dioxide for adjusting the pH of said pulp suspension and for maintaining the pH at a desired level throughout the paper making;
- forming said pulp suspension into a web; and
- drying said web to form paper.

12. Process according to claim 14, characterized in that the pH of said pulp suspension is adjusted to a desired value between 7 and 9 by adding an excess of said alkali metal hydroxide or said carbon dioxide.

**DECLARATION AND POWER OF ATTORNEY  
FOR UTILITY OR DESIGN PATENT APPLICATION**

☐ Submitted with Initial Filing

☒ Submitted after Initial Filing  
(Surcharge (37 CFR 1.16(e)) required)

Attorney Docket No.: 32107

Application Number: 09/445,710

First Named Inventor: Hannu Juhani Leino

Filing Date: December 9, 1999

Group Art Unit: \_\_\_\_\_

Examiner Name: \_\_\_\_\_

**As a below named inventor, I hereby declare that:**

My residence, post office address, and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

**A PROCESS FOR STABILIZING THE pH OF A PULP SUSPENSION  
AND FOR PRODUCING PAPERS FROM THE STABILIZED PULP**

the specification of which (check only one item below)

☐ is attached hereto,

OR

☒ was filed on (MM/DD/YYYY) December 9, 1999 as United States Application Number or PCT International Application Number 09/445,710 and was amended on (MM/DD/YYYY) \_\_\_\_\_ (if applicable).

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56.

09445710.031300

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d), or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, any foreign application for patent or inventor's certificate, or any PCT international application having a filing date before that of the application on which priority is claimed.

<u>Country</u>	<u>Prior Foreign Application Number(s)</u>	<u>Foreign Filing Date (MM/DD/YYYY)</u>	<u>Priority Claimed?</u>
Finland	972522	June 13, 1997	Yes

As a named inventor, I hereby appoint each of the following as my attorneys with full power of substitution and revocation, to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

Charles B. Gordon, Reg. No. 16923  
William C. McCoy, Reg. No. 16885  
Richard H. Dickinson, Jr., Reg. No. 18622  
Thomas P. Schiller, Reg. No. 20677  
David B. Deioma, Reg. No. 22841  
Joseph J. Corso, Reg. No. 25845  
Howard G. Shimola, Reg. No. 26232

Jeffrey J. Sopko, Reg. No. 27676  
John P. Murtaugh, Reg. No. 34226  
James M. Moore, Reg. No. 32923  
David E. Spaw, Reg. No. 34732  
Michael W. Garvey, Reg. No. 35878  
Paul R. Katterle, Reg. No. 36563  
Richard M. Mescher, Reg. No. 38242  
M. David Galin, Reg. No. 41767

Address all correspondence to Customer Number 000,116.

Please direct all correspondence and inquiries to Jeffrey J. Sopko at (216) 579-1700.



I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

(1) Inventor Name (joint): Hannu Juhani Leino

Signature: *Hannu Leino*

Date: FEB 3 2000

Citizenship: Finland

Residence: Espoo, Finland

Post Office Address: Kalastajankuja 8 E 35, FIN-02230 Espoo, Finland

(2) Inventor Name (joint): Anna Linnea Holmberg

Signature: *Anna Holmberg*

Date: January 31, 2000

Citizenship: Sweden

Residence: Lidingö, Sweden

Post Office Address: Odenvägen 12, S-181 22 Lidingö, Sweden